



crashwrap.com

**Process Information Grids
Standard Operating Procedure**

Storage Directions:

Process Information Grids (PIGs) features an adhesive designed specifically for automotive aftermarket applications. Process Information Grids need to be stored at room temperature. Warm film will stick to a cold window. Film stored below 60 degrees will not stick to anything.

Please read the application directions below to ensure that you are storing and applying Process Information Grids correctly.

Application Directions:

Carefully clean the window with glass cleaner before you apply the process Information Grid. The car must be clean of any snow or frost prior to application. Although the film will adhere to clean cold and/or wet surfaces the film adheres best when the surface is clean, warm and dry.

- It is best to use a towel to smooth the film to the vehicle window.
- Install the PIG with slight tension, loosely installed film is subject to being removed by the wind.
- Adhere to a side window, installing on the windshield may block forward vision.
- For best results we recommend using a Sharpie Oil Based Paint Marker or China Marker often referred to as grease pencils.
- Store Process Information Grids in the box in a dry area. Extended exposure to humidity will cause the adhesive to fail.
- Our adhesive is water born and will not remove with solvent based cleaners. In rare instances of adhesive transfer use ammonia based glass cleaners or isopropyl alcohol to remove
- Warning: DO NOT USE on flexible plastic windows such as those found on convertible tops as discoloration has been known to occur!

Haldon Company 1651 Aucutt Rd. Montgomery, IL 60538 (630) 264-2527

Please contact Haldon Company with any technical questions.

Mike@Crashwrap.com